



Flange dimensions DIN 2501 page 1	DN	PN	L	D	g	K	b	z	d	H1	øA	Mass	Order-No.
	mm	bar	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
PN 10 Flanged ends raised face*	250	10	650	395	320	350	26	12	22	385	60	230	FKK V 010.250
	300	10	750	445	370	400	26	12	22	427	60	420	FKK V 010.300
PN 16 Flanged ends raised face*	250	16	650	405	320	355	26	12	26	385	60	240	FKK V 016.250
	300	16	750	460	378	410	28	12	26	427	60	430	FKK V 016.300
PN 25 Flanged ends raised face*	250	25	650	425	335	370	32	12	30	385	60	255	FKK V 025.250
	300	25	750	485	395	430	34	16	30	427	60	445	FKK V 025.300

Materials	PN	DN	Type 1	Type 2
Body	10-25	250-300	Steel	Steel
Ball	10-25	250-300	Spheroidal cast iron, hard chromed	Spheroidal cast iron, hard chromed
Seals	10-25	250-300	NBR	PTFE

**Please quote order-no. and type:
FKK V XXX.XXX / Type (1 o. 2)**



- With DIN DVGW acceptance for gas.
- Delivery without handle; by request with gear operator, pneumatic or electric drive.
- Ball valves with PTFE seals are normally delivered with FPM O-rings.
- Special designs upon requests.

Also available with TÜV component approval

* Further types of flange gasket facings on demand